



- H.264 Dual-Stream Video Compression.
- Compatible with Analog 960H/D1.
- All Channel 720P@25/30FPS Realtime Recording, 1/4CH Playback Simultaneously.
- 2\*USB2.0, USB Disk Up to 32G(Kingston)
- Audio Talk Back Supported.
- Support 10M/100Mbit/s Network Interface.
- Mobile Surveillance Supported, Including iPhone, iPad, Android.
- Support Browser IE 6.0 Above.
- Free ISS PC, ISS Mobile Management software.
- Free DDNS Server: HDCCTVDDNS.
- 1080P HD Display.
- 1HDD\* Max 2TB per HDD.

MODEL	QH-D6008CM
Operation System	Linux
<b>VIDEO</b>	
Video System	NTSC/Pal Switch Selectable
Input	BNC*8, 1.0Vp-p, 75ohm
CVBS Output	NTSC:720*480
HDMI Output	1 HDMI Output
VGA Output	1 VGA Output
<b>AUDIO</b>	
Input	4ch, RCA
Output	1ch, RCA
Talk Back	Yes
<b>CONTROL</b>	
Mouse	2*USB2.0

IR Controller	Yes
<b>STORAGE</b>	
Build In Interface	SATA 2.6 *1 (1*HDD max 4TB)
<b>DISPLAY</b>	
Division	1, 4, 9
Zoom	Preview & Playback Zoom Support
<b>RECORDING</b>	
Compression	H.264 (High profile)
Recording Mode	Manual/Schedule/Motion Detection/Sensor (Optional)
Encoding Ability	NA
Decoding Ability	NA
Resolution	Mode 1: 8CH 720P
	Mode 2: 4CH 720P + 4CH 960H
	Mode 3: 8CH 960H
Record Frame Rate	8CH 720P@20fps
Quality	Worst, Worse, Bad, Normal, Better, Best
<b>PLAYBACK</b>	
Sync Playback	1, 4
Speed	Normal, FF (1X, 2X, 4X, 8X,), Slow (1/2X, 1/4X, 1/8X)
Search Method	Time, Event, Channels and Calendar
<b>COMMUNICATION</b>	
Remote Access	IE ( 10.0 and below ), ISS ( Windows XP/WIN7/WIN8/WIN10 ), ISS MOBILE2 ( IOS, Android )
Remote Operation	Remote View, Remote Playback, Remote Setup
Network Service	TCP/IP, PPPOE, DDNS, FTP, NTP UPNP
Mobile Device	iPone, iPad, Android
Wan Rj45	10/100Mbit/s
3g External Module	Yes, with USB 2.0 Port
Wifi External Module	Yes, with USB 2.0 Port, 100Meters
GUI Interface	Supported GUI 16 Bit True Color
PTZ Protocol	PELCO-D, PELCO-P, etc 17 kinds of protocol
<b>BACKUP</b>	

Internal	NA
External	2*USB2.0
Network	YES
File Format	AVI
<b>GENERAL</b>	
Alarm In/Out	NA
Rs-485	1
Rs-232	NA
Unit Dimension(mm)	260 (L) x 44 (H) x 221 (W)
Operation Temperature	10°~ 40°
Working Humidity	10% ~ 90%
Power Consumption	DC 12V, 2A, <6W (Exclude HDD)