

## Feature



- Third-party IP cameras supported with ONVIF conformance
- 32 channel IP camera input
- Compatibel with QIHAN free DDNS
- Support UPnP, NTP, DHCP, PPPoE
- Up to 5 Megapixels resolution recording, storage and playback
- Simultaneous HDMI and VGA output, the resolution is up to 1080P
- Up to 16 channels synchronously playback
- Support instant playback
- Support corridor mode

Model No.	QH-N6332F-H
<b>VIDEO/AUDIO INPUT</b>	
IP Video Input	32 CH
Two-way Audio Input	1 CH, RCA (2.0 Vp-p, 1kΩ)
<b>NETWORK</b>	
Incoming Bandwidth	200Mbps
<b>VIDEO/AUDIO OUTPUT</b>	
HDMI Output	1
VGA Output	1
Audio Output	1 CH, RCA
<b>DECODING</b>	
Live View / Playback Resolution	4MP/3MP/1080P/960P/720P/VGA/D1/CIF
Recording Resolution	4MP/3MP/1080P/960P/720P/VGA/D1/CIF
Synchronous Playback	Max. 16CH 720P or 6CH 1080P or 3CH 4MP
<b>HARD DISK DRIVE (HDD)</b>	
SATA	2
Capacity	Up to 4TB for each disk
<b>EXTERNAL INTERFACE</b>	
Network Interface	2RJ-45 10/100/1000Mbps self-adaptive Ethernet interface
Serial Interface	1 RS-232, 1 RS-485
USB Interface	2 USB 2.0 + 1 USB 3.0
Alarm In	8
Alarm Out	2
<b>PoE</b>	
Interface	NA
Supported Standard	NA

<b>GENERAL</b>	
Power Supply	220V, AC
Consumption	20W (Without Disk), 90W (Fully Configured)
Working Temperature	-10°C ~ 55°C (14°F ~ 131°F)
Working Humidity	10% - 90%
Dimensions	86.1mm × 442.0mm × 421.0mm, (3.39" × 17.40" × 16.75"), 2U
Weight (without HDD)	5.5KG