



Model	QH-3126HC-N/QH-3126HC-NO
CAMERA	
Image Device	1/4" HD CMOS
TV System	PAL/NTSC
Total Pixels	1.0M Pixels
Effective Pixels	1280 (H) * 720 (V)
Scanning System	Progressive
Synchronization	Internal
Min. Illumination	0 Lux (LED on)
S/N Ratio	>58db
Video Output	1Vp-p, 75ohm, BNC
LENS	
Focal Length	2.8MM 3.6MM or 6MM Fixed Lens
OPERATIONAL (For OSD Model)	
LENS	DC/MANUAL
Shutter	Auto, 1/25-30(FLK)
AGC	0-15
SENS-UP	ON/OFF
Brightness	0-100
D-WDR	ON/OFF
Defog	ON/OFF
Backlight	ON/OFF

White Ball	ATW/Indoor/Outdoor
Day & Night	EXT/Color/B/W/Auto
IR Smart	Yes
2DNR/3DNR	Yes
Cam Title	Yes
D-Effect	Freeze/Mirror
Motion	4 Area
Privacy	4 Area
Language	CHN1/CHN2/GER/FRA/ITA/SPA/POL/RUS/POR/NED/TUR
Defect	Live DPC/White DPC/Black DPC
Infrared LED	24EA
IR Distance	10 ~ 20 Meters
IR-CUT	YES
Infrared Spectrum	850nm
OPERATIONAL	
Operation Temperature	-10°C~ +60°C
Storage Temperature	-20°C~ +70°C
Water-proof Casing	Vandal proof
ELECTRICAL	
Max Power	4.72W
Adapter Requirement	DC12V 1A
MECHANICAL	
Color	White
Dimensions	95*73MM
Net Weight	370g/pcs
Transmission distance	500meters (75-3)