



Feature

- H.265 video compression
- Third-party IP cameras supported with ONVIF conformance
- Support PnP for easy IPC discovery and usage
- Up to 8 Megapixels resolution recording, storage and playback
- Support 2-ch HDMI, 1-ch VGA, 1-ch CVBS, HDMI2 is up to 4K(3840x2160) resolution
- Up to 16 channels synchronously playback
- Support instant playback
- Support corridor mode
- 8 SATA HDDs up to 48TB
- Support eSATA Interface

Model	QH-N6564F-H
VIDEO / AUDIO INPUT	
IP Video Input	64 CH
Two-way Audio Input	1 CH, RCA (2.0 Vp-p, 1kΩ)
NETWORK	
Incoming bandwidth	320Mbps
Outgoing bandwidth	320Mbps
Remote connection	16
VIDEO / AUDIO OUTPUT	
HDMI Output	2
VGA Output	1
CVBS Output	1, BNC
Audio Output	1 CH, RCA
DECODING	
Live View/Playback Resolution	8MP/6MP/5MP/4MP/3MP/1080P/960P/720P/VGA/D1/CIF
Recording Resolution	8MP/6MP/5MP/4MP/3MP/1080P/960P/720P/VGA/D1/CIF
Synchronous Playback	16 CH 4 x 4K@30, 8 x 4MP@20, 16 x 1080P@25, 32 x 720P@25, 64 x D1
HARD DISK DRIVE	
Sata	8
Capacity	Up to 6TB for each disk
EXTERNAL INTERFACE	
Network Interface	2RJ-45 10/100/1000Mbps self-adaptive Ethernet interface
Serial Interface	1 RS-232, 1 RS-485

USB Interface	1 USB2.0 + 1 USB3.0
eSATA Interface	1
Alarm In	16
Alarm Out	4
PoE	
Interface	NA
Max. Power	/
Supported Standard	NA
GENERAL	
Power Supply	100~240V, AC
Consumption	≤ 20W (Without Disk)
Working Temperature	-10°C ~ 55°C (14°F ~ 131°F)
Working Humidity	10%~90%
Dimensions	86.1mm × 442.0mm × 425.5mm (3.39" × 17.40" × 16.75"), 2U
Weight (without HDD)	5.13KG