



Feature

- AHD lossless video output.
- HD CCD progressive scan, perfectly capture the moving object.
- High speed, long distance, real time transmission.
- Auto color to B / W at low illumination.
- Support ICR switch, true day / night.
- Support noise reduction function.
- 10 ~ 20m IR night view distance.
- IP66 waterproof
- IP65 ingress protection.

| Model | QH-3505HC-NO |
|---------------|------------------------------------|
| CAMERA | |
| Image Device | 1/4" HD CCD |
| TV System | PAL/NTSC |
| Total Pixels | 1280 (H) x 800 (V) |
| Frame Rate | 25/30 fps @ 720p |
| Max. distance | 500m |
| OSD | Yes |
| BLC | Low/Middle/High |
| Shutter Mode | Auto / Manual |
| LENS | |
| Focal Length | 3.6MM HD |
| LENS | DC/MANUAL |
| Shutter Speed | 1/100 000 - 1/50; 1/100 000 - 1/60 |
| AGC | Low/Middle/High |
| AWB | ATW1/ATW2/ATW3 |
| Sharpness | 0-100 |
| HDNR | 0 -100 |
| Contrast | 0 -100 |
| Saturation | 0 -100 |
| R Gain | 0 -100 |
| G Gain | 0 -100 |

| | |
|-----------------------|--|
| B Gain | 0 -100 |
| Day&Night | EXT/Color/B/W/Auto |
| Language | Eng / Chn |
| Camera | Low/Middle/High |
| Bright | Low/Middle/High |
| Bad Pixel | Low/Middle/High |
| Privacy Mask | 42384 |
| HLC | 0 - 100 |
| Min. Illumination | 0Lux (IR ON) |
| S/N Ratio | >50dB (AGC off) |
| NR | 2DNR |
| Voltage | DC 12V |
| Current | 190mA± 15% (IR ON); 70mA±15% (IR OFF); |
| IR Led | 24pcs |
| IR Range | 25m |
| Water-proof Casing | IP 65 |
| Storage temperature | -20°C~+70°C |
| Operation Environment | -10°C~+50°C RH90% MAX |
| Size | 97*82MM |
| Weight | 200g/pcs |