



<b>Model No.</b>	<b>QH-IP6121FA-7-H18</b>
<b>Resolution</b>	18X Optical Zoom
<b>Zoom Lens</b>	HITACHI DI-SC110, 1/3" Megapixel Progressive Scan Ex-View Color CCD,800 TV Lines of Resolution, 18X Optical Zoom F1.6 and practical f value 4.7-84.6mm
<b>OPERATION</b>	
<b>OSD menu</b>	English, Chinese, Spanish, Russian Optional
<b>Preset position</b>	256 Preset Positions
<b>Scan</b>	Auto scan and left-right limited scan, speed adjustable
<b>Patrol</b>	8 tracks, preset, speed and dwell time changeable
<b>Pattern</b>	6 Lines(Pan/Tilt/Zoom, every line can record up to 120 seconds)
<b>Alarm</b>	4 or 8 alarm inputs optional, 2 alarm outputs
<b>Password protection</b>	YES
<b>Temperature display and Settings</b>	YES(Temperature alarm set, Temperature Display)
<b>Authority Management</b>	YES
<b>Private masking</b>	8 zones
<b>Address range</b>	0~255 (Setup by dip switcher, firmware and network)
<b>Communication</b>	RS485 (+/-)
<b>Baud rate</b>	2400/4800/9600/19200, setup by dip switcher
<b>Protocol</b>	PELCO-D, PELCO-P , ULTRACK, VICON, DYNACOLOR
<b>Device title</b>	Display on/off
<b>Zoom times</b>	Display on/off
<b>MECHANICAL</b>	
<b>Pan range</b>	0°~ 360° continuously

<b>Pan speed</b>	0.1~ 360°/s
<b>Tilt range</b>	0°~ 180° auto flip on/off performance
<b>Tilt speed</b>	0.1~ 180°/s
<b>Precision</b>	±0.10°
<b>OTHERS</b>	
<b>Housing</b>	Aluminum alloy, vandal proof housing,Wall Mount,Ceiling Mount
<b>Lighting proof</b>	6000V
<b>Water proof</b>	IP67
<b>Work temp</b>	-40°C~+60°C
<b>Work humidity</b>	0%~90%
<b>Power</b>	24V AC 2A 60Hz/50Hz 35W