



- H.264 Dual-Stream Video Compression.
- Compatible with AHD 1080P, AHD 720P, Analog 960H/D1.
- AHD New Technology 1080N (960x1080) Decoding & Recording, 1080P Image Quality While Save 50% Storage Space.
- 2*USB2.0, USB Disk Up to 32G(Kingston)
- Audio Talk Back Supported.
- Support 10M/100Mbit/s Network Interface.
- Mobile Surveillance Supported, Including iPhone, iPad, Android.
- Support Browser IE 6.0 Above.
- Free ISS PC, ISS Mobile Management software.
- Free DDNS Server: HDCCTVDDNS.
- HDMI & VGA 1080P HD Display.
- Max 4TB per HDD.

MODEL	QH-D6008CH
Operation System	Linux
VIDEO	
Video System	NTSC/Pal Switch Selectable
Input	BNC*8, 1.0Vp-p, 75ohm
CVBS Output	1 CVBS Output
HDMI Output	1 HDMI Output
VGA Output	1 VGA Output
AUDIO	
Input	4ch, RCA
Output	1ch, RCA
Talk Back	Yes
CONTROL	
Mouse	2*USB2.0

IR Controller	Yes
STORAGE	
Build In Interface	SATA *1 (1*HDD max 4TB)
DISPLAY	
Division	1, 4, 9
Zoom	Preview & Playback Zoom Support
RECORDING	
Compression	H.264 (High profile)
Recording Mode	Manual/Schedule/Motion Detection/Sensor (Optional)
Encoding Ability	8*1080N@15fps
Decoding Ability	4*1080N@15fps
Resolution	Analog : 8*1080N, Hybird : 4*1080N (Analog)+4*720P (Network), Network : 8*720P
Quality	Worst, Worse, Bad, Normal, Better, Best
PLAYBACK	
Sync Playback	1, 4
Speed	Normal, FF (1X, 2X, 4X, 8X,), Slow (1/2X, 1/4X, 1/8X)
Search Method	Time, Event, Channels and Calendar
COMMUNICATION	
Remote Access	IE (10.0 and below), ISS (Windows XP/WIN7/WIN8/WIN10), ISS MOBILE2 (IOS, Android)
Remote Operation	Remote View, Remote Playback, Remote Setup
Network Service	TCP/IP, PPPOE, DDNS, FTP, NTP UPNP
Mobile Device	iPone, iPad, Android
Wan Rj45	10/100Mbit/s
3g External Module	Yes, with USB 2.0 Port
Wifi External Module	Yes, with USB 2.0 Port, 100Meters
GUI Interface	Supported GUI 16 Bit True Color
PTZ Protocol	PELCO-D, PELCO-P, etc 17 kinds of protocol
BACKUP	
Internal	NA
External	2*USB2.0

Network	YES
File Format	AVI/DAV
GENERAL	
Alarm In/Out	NA
Rs-485	1
Rs-232	NA
Unit Dimension(mm)	260 (L) x 44 (H) x 221 (W)
Operation Temperature	10°~ 40°
Working Humidity	10% ~ 90%
Power Consumption	DC 12V, 2A, <6W (Exclude HDD)